


REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-018	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 1997		3. REPORT TYPE AND DATES COVERED
4. TITLE AND SUBTITLE Advanced Fuel Hydrocarbon Remediation National Test Location - Demonstration of Hot Air Vapor Extraction for Fuel Hydrocarbon Cleanup			5. FUNDING NUMBERS	
6. AUTHOR(S) Jeff Heath and Ernie Lory				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESSE(S) Naval Facilities Engineering Service Center Port Hueneme, CA 93043-4370			8. PERFORMING ORGANIZATION REPORT NUMBER TDS-2015-ENV (Revised)	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESSES			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Hot air vapor extration (HAVE) is a fast-track, innovative environmental cleanup technolgy that uses a combination of thermal, heap pile, and vapor extration techniques to remove and destroy hydrocarbon contamination in soil. This technology is very effective in cleaning soils contaminated with gasoline, diesel, heavy oil, and polycyclic aromatic hydrocarbons (PAH). 19970411 019				
14. SUBJECT TERMS Hot air vapor extraction (HAVE), polycyclic aromatic hydrocarbons (PAH).			15. NUMBER OF PAGES 3	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	

DISCLAIMER NOTICE




THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF COLOR PAGES WHICH DO NOT REPRODUCE LEGIBLY ON BLACK AND WHITE MICROFICHE.



TechData Sheet

Naval Facilities Engineering Service Center
Port Hueneme, California 93043-4370



TDS-2015-ENV (Revised)

March 1997

Advanced Fuel Hydrocarbon Remediation National Test Location

Demonstration of Hot Air Vapor Extraction for Fuel Hydrocarbon Cleanup

Conducted by:

Naval Facilities Engineering Service Center, Port Hueneme, CA
and
Sound Remedial Technologies, Inc., Duvall, WA

Hot air vapor extraction (HAVE) is a fast-track, innovative environmental cleanup technology that uses a combination of thermal, heap pile, and vapor extraction techniques to remove and destroy hydrocarbon contamination in soil. This technology is very effective in cleaning soils contaminated with gasoline, diesel, heavy oil, and polycyclic aromatic hydrocarbons (PAH).

Purpose of the Demonstration

The HAVE system demonstration is designed to yield:

1. Performance capability of the system in cleaning fuel hydrocarbon contaminants in soil.
2. Cost data for use in implementation of the system.
3. Optimized design parameters for the system by using computer modeling.
4. Operational test report and other technology transfer documents to assist Government agencies use the technology.

Advantages of Hot Air Vapor Extraction Technology

The HAVE technology has the following distinct advantages:

- **A simple but expeditious cleanup process.** The entire HAVE system is trailer-mounted and is ready for deployment once the heap pile is constructed. Cleanup time for 500 cubic yards of a diesel fuel contaminated pile is approximately 7 days.
- **An effective cleanup technology.** Capable of cleaning soils to below the regulatory required limits or to non-detectable levels.
- **A low cost alternative.** The treatment costs may be one third lower than those of the conventional thermal technologies.
- **Fuel hydrocarbon cleanup.** The contaminants removed are completely destroyed.
- **Clean air emissions.** The exhausts from the HAVE system are cleaner than most automobiles' exhausts.

Description

The HAVE system is an off-site thermal treatment technology for the remediation of hydrocarbon contaminants in soils, including gasoline, diesel, heavy oil, and polyaromatic hydrocarbon (PAH).

As with other off-site technologies, the contaminated soil needs to be excavated before treatment. The excavated soil is then built into a pile containing ducts for hot air distribution and vapor extraction. (See Figure 1.) The soil pile is covered and sealed with a sheet of heavy duty silicone membrane.

After the soil pile is constructed, the ducts are connected to the HAVE system, which is mounted in a trailer. (See Figure 2.) The main components of the HAVE system include a:

- Burn chamber
- Vapor blower
- Hot air blower
- Catalytic oxidizer
- Control panels for displaying and recording various monitoring parameters




Figure 1. Soil is built into a pile containing ducts for hot air distribution and vapor extraction.



Figure 2. Soil pile is covered by a membrane and ducts are connected to the HAVE system located in the trailer.

The burner is fueled by propane or natural gas to heat the air. The hot air coming out of the burner is fed into the soil pile through the distribution ducts to volatilize the contaminants and is removed from the pile through the extraction ducts back into the burner. The hydrocarbon vapor that is removed from the pile is destroyed in the burner through the combustion process. Due to the heating values contained in the hydrocarbon, the contaminants in the vapor become a secondary fuel for the combustion in the burner, thus reducing the amounts of propane or natural gas required to feed the burner.

The burner was designed to retain the vapor for approximately 0.7 second, long enough to completely destroy the contaminants. The cleaned hot air is then fed back into the soil pile to continue the cycle. Since the oxygen available in the burner for combustion is depleted as the process progresses, fresh air is drawn into the burner to supply the necessary oxygen for combustion. The excess air built up in the system (approximately 15 percent) is vented through a bank of catalytic converters to remove the residual vapor contaminants before being released into the atmosphere. These exhausts are cleaner than those from most automobiles. Also, the operating temperature within the pile ranges between 200 and 350°F although the temperature in the burner can be as high as 1,800°F.

The HAVE system is equipped with various sensors to monitor the temperatures, air and vapor flow rates, hydrocarbon vapor, and the air emissions.

During the demonstrations, soil samples will be collected and analyzed daily to monitor the cleanup progress. After achieving the prevailing regulatory cleanup standards, the soils can be back-filled into the original sites.

For more information about the *HAVE system*, contact:

Mr. Jeff Heath

Manager, Technology Application Branch
(805) 982-1657, DSN: 551-1657,
Internet: jheath@nfesc.navy.mil

or

Mr. Ernie Lory

Manager, Advanced Fuel Hydrocarbon Remediation
National Test Location
(805) 982-1299, DSN: 551-1299,
Internet: elory@nfesc.navy.mil

*Our Web address is: <http://www.nfesc.navy.mil>
For technical assistance, call 1-888-4 THE ESC
(1-888-484-3372)*